Microchip Atmel

RF Identification

Cloud Partners

Drivers and Sensors Security ICs **Programmable Logic**

Digital Broadcast

Microcontroller Selector

Smart Energy

Memory

Analog

Rad Hard

IR Control

- O	4	Products	Applications	Technologies	Support	Abou
Microcontrollers	Home > Products > Wi	reless Connectivity >	· Wi-Fi > SmartConnect	:		
Touch Solutions			_			
Automotive	WINC3400 X	plained PRO	Starter Kit			
Wireless Connectivity						
Bluetooth	Overview	Devices	Documents	Applications	Related Tool	s
802.15.4	*					
Wi-Fi				4		
SmartConnect	NEW th S	00	E	H	C C	
SmartDirect	Bluetoou		A C		Get Sta	arted
Smart RF	WI-FILL		.0 9		📕 We'll tell	l you a
SigFox	N.L. NA			and	Y know to	start e

New Wi-Fi/Bluetooth Combo Solution for lo

Atmel[®] SmartConnect Platform

WILC3000)

Buy Now

The Atmel® ATWINC3400-XSTK evaluation kit is a hardware platform to evaluate the Atmel® WINC3400-MR210CA module and CRTX-M0+ referance.

Atmel® SmartConnect-WINC3400 is an IEEE 802.11 b/g/n/BLE4.0 IOT network controller SoC. It is the ideal add-On to existing MCU solutions bringing WiFi and BLE Network capabilities through UART or SPI-to-WiFi interface. The WINC3400 connects to any Atmel AVR or SMART MCU with minimal resource requirements. The WINC3400

most advanced mode is a single stream 1x1 802.11n mode providing up to 72 Mbps PHY throughput. WINC3400 features fully integrated Power Amplifier, LNA, Switch and Power Management. ATWINC3400 also features an on-chip microcontroller and integrated flash memory for system software with built in coexistence mechanism for concurrent Wi-Fi & BLE functionality. The only external clock source needed for the WINC3400 is a high-speed crystal or oscillator with a wide variety of reference clock frequencies supported (between 12 - 32 MHz). The WINC3400 is available in a QFN package.

Key Features

- IEEE 802.11: IEEE 802.11 b/g/n 20MHz (1x1) solution
- IEEE 802.11: Single spatial stream in 2.4GHz ISM band
- IEEE 802.11: Integrated PA and T/R Switch
- IEEE 802.11: Superior Sensitivity and Range via advanced PHY signal processing
- IEEE 802.11: Operating temperature range of -40°C to +85°C
- IEEE 802.11: On-Chip Network Stack to offload MCU
- IEEE 802.11: Integrated Network IP stack to minimize host CPU requirements
- IEEE 802.11: Network features: TCP, UDP, DHCP, ARP, HTTP, SSL, and DNS
- Bluetooth: On-Chip Network Stack to offload MCU
- Bluetooth: BLE 4.0
- Bluetooth: Class 1 & 2 transmission
- Bluetooth: Adaptive Frequency Hopping
- Bluetooth: HCI (Host Control Interface) via high speed UART
- Bluetooth: Integrated PA and T/R Switch
- Bluetooth: Superior Sensitivity and Range
- WINC3400-SHIELD: SPI support
- WINC3400-SHIELD: Power supply
- WINC3400-SHIELD: Debug headers

Ordering Information

Ordering Code	Atmel Store Availability ¹	Unit Price ²	Buy Online
ATWINC3400-XSTK		Varies	<u>Check Distributor</u>

¹Backlog orders can be placed for items currently not available. ²Suggested retail price per unit for budgetary use only.



Downloaded from Arrow.com.



now to start evaluating and working with this product.

About

Buy

Ы

Ы

Ы

» Start Now

- » Contact Sales
- » Sign-up for News

Related Items

- » 802.11 Forum
- » Technical Support
- » What's Changed
- » Mature Devices



Contact Subscribe Jobs Site Use Terms Privacy Cookies Sales Terms © 2016 Atmel Corporation

- Products
 - Microcontrollers Touch Solutions Automotive Wireless Connectivity Smart Energy Memory Drivers and Sensors Security ICs Programmable Logic Analog Rad Hard Digital Broadcast
- Applications Automotive Building Automation Home Appliances Home Entertainment Industrial Automation Lighting Internet of Things (IoT) Smart Energy Mobile Electronics PC Peripherals Wearables

Support

- Boards and Kits Tools and Software Development Tools Document Library Training Support Resources Third-Party Tools/Support Design Consultants
- About Corporate Press Room Contact Atmel Investors Careers Suppliers Embedded Design Blog Quality Compliance

Contact Atmel Buy

Atmel Store FAQs Technical Support Communities