


Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > DDR I and DDR II Buffers > Fan-out Buffers > 93789 > 93789DFLF

[Add to myIDT \[?\]](#)

You may also like...



## 93789DFLF

**Category:** Fan-out Buffers

**Generic Part:** 93789

**Market Group:** PC CLOCK

**Description:** PC BUFFER

Recommended Application: DDR fan out buffer for VIA P4x266/400 & PT800/880 chipsets  
 Product Description/Features:  
 • Max. frequency supported: 266 MHz (DDR533)  
 • Low skew, fanout buffer  
 • 1 to 6 differential clock distribution  
 • I2C for functional and output control  
 • Feedback pin for input to output synchronization  
 • Supports up to 2 DDR DIMMs  
 • CMOS level control signal input

### Parameters

Package	SSOP 28 (PYG28)
Voltage	3.3 V
Package	SSOP 28
Speed	NA
Temperature	C
Status	Active
Sample	Yes
Minimum Order Quantity	141
Factory Order Increment	47

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Description	SSOP 5.3 MM
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	NA
Length	10.2
Mark	PYG
Width	5.3
Pitch	0.65
Thickness	1.73
Status	Active