RoHS Reach Halogen Free Pb Free



ACM1513-551-2PL-TLHF

| 用途 | 一般等级 |
|----|--------------------------------------|
| 特点 | Wire Wound <mark>绕线 Power</mark> 电源线 |
| 系列 | ACM |
| 状态 | 量产体制 |
| 品牌 | TDK |



| | 尺寸 |
|---------|-----------------------|
| 长度(L) | 15.00mm ± 0.40 mm |
| 宽度(W) | 13.00mm ±0.40mm |
| 厚度 高低 | 6.00mm Max. |

| 电气特性 | |
|-------------|-----------------------------------|
| 共模阻抗 [Typ.] | 550Ω at $100 MHz$ |
| 共模阻抗 [Min.] | 450Ω at $100 \mathrm{MHz}$ |
| 共模电感 | 1.1µH at 1MHz (参考) |
| 额定电流 | 10A |
| 额定电压 | 50VDC |
| 绝缘电阻 [Min.] | 10ΜΩ |
| 直流电阻 | 4mΩ Max. |

| ţ | 其他 |
|----------|------------------------|
| 使用温度范围 | -40∼85° C |
| 焊接方法 | 回流 烙铁焊接 |
| AEC-Q200 | NO |
| 包装形式 | 塑封编带 (330mm卷筒、帯宽 24mm) |
| 包装个数 | 500pcs |
| 重量 | 3. 14g |

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free




特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.