ACM2012-121-2P-T002

RoHS Reach Halogen Free Pb Free

用途	一般等级
特点	Wire Wound <mark>绕线</mark> High-speed <mark>高速信号线</mark>
系列	ACM
状态	量产体制
品牌	TDK



	尺寸
长度(L)	2.00mm ± 0.20 mm
宽度(W)	1. 20mm ±0. 20mm
厚度 高低	1. $20mm \pm 0.10mm$

电气特性		
共模阻抗 [Typ.]	120Ω at 100MHz	
共模阻抗 [Min.]	90Ω at 100MHz	
共模电感		
额定电流	370mA	
额定电压	50VDC	
绝缘电阻 [Min.]	10ΜΩ	
直流电阻	220mΩ Max.	

	其他
使用温度范围	-40∼85° C
焊接方法	回流
汗 按刀14	烙铁焊接
AEC-Q200	NO
包装形式	塑封编带 (180mm卷筒、帯宽 8mm)
包装个数	2000pcs
重量	0.01g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free



ACM2012-121-2P-T002


特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.