ACM2012-361-2P-T001

RoHS Reach Pb Free

用途	车载等级
特点	Wire Wound <mark>绕线</mark> AEC-Q200 AEC-Q200
系列	ACM
状态	量产体制
品牌	TDK



	尺寸
长度(L)	2.00mm ± 0.20 mm
宽度(W)	1. 20mm ±0. 20mm
厚度 高低	1. $20mm \pm 0.10mm$

电	气特性
共模阻抗 [Typ.]	360Ω at 100MHz
共模阻抗 [Min.]	270Ω at 100MHz
共模电感	
额定电流	220mA
额定电压	50VDC
绝缘电阻 [Min.]	10ΜΩ
直流电阻	500mΩ Max.

į	其他
使用温度范围	-40∼105° C
焊接方法	回流 烙铁焊接
AEC-Q200	YES
包装形式	塑封编带 (180mm卷筒、带宽 8mm)
包装个数	2000pcs
重量	0.01g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



Creation Date : November 15, 2021 (GMT)

RoHS Reach Pb Free

特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.


 $^{!\ \}mbox{\footnotements}$. All specifications are subject to change without notice.

ACM2012-361-2P-T001 RoHS Reach Pb Free

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.