RoHS Reach Halogen Free Pb Free



品牌

ACM2012E-121-2P-T01

用途	一般等级
特点	Wire Wound <mark>绕线 High-speed</mark> 高速信号线
系列	ACM
	A 停止生产
	推荐代替型号 : ACM2012H-121-2P-T05 (不保证其兼容性。)
状态	停产发布日期 : 2019年12月3日
	最后订单日期 : 2020年9月30日

最后出货日期 : 2021年9月30日

TDK



	尺寸
长度(L)	$2.00 \text{mm} \pm 0.20 \text{mm}$
宽度(W)	1. 20mm ±0. 20mm
厚度 高低	1.00mm ±0.10mm

电气特性	
共模阻抗 [Typ.]	120Ω at 100MHz
共模阻抗 [Min.]	90Ω at 100MHz
共模电感	230nH at 1MHz (参考)
额定电流	270mA
额定电压	50VDC
	10ΜΩ
直流电阻	650mΩ Max.

	其他
使用温度范围	-40∼85° C
阳水子六十	回流
焊接方法	烙铁焊接
AEC-Q200	NO
包装形式	塑封编带 (180mm卷筒、带宽 8mm)
包装个数	2000pcs
重量	0.008g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{!\ \}mbox{\footnotements}$. All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free



ACM2012E-121-2P-T01


特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.