ACM2012H-900-2P-T05

用途	一般等级
特点	Wire Wound <mark>绕线</mark> Ultra 超高速信号线
系列	ACM
状态	量产体制
品牌	TDK



	尺寸
长度(L)	2.00mm $\pm 0.20$ mm
宽度(W)	1. 20mm ±0. 20mm
厚度   高低	1. $20mm \pm 0.10mm$

<b>4</b>	3.气特性
共模阻抗 [Typ.]	$90\Omega$ at $100 MHz$
共模阻抗 [Min.]	65Ω at 100MHz
共模电感	
额定电流	300mA
额定电压	20VDC
绝缘电阻 [Min.]	10M Ω
直流电阻	300mΩ Max.

其他		
使用温度范围	-40∼85° C	
焊接方法	回流 烙铁焊接	
AEC-Q200	NO	
包装形式	塑封编带 (180mm卷筒、带宽 8mm)	
包装个数	2000pcs	
重量	0.01g	

<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

 $<sup>!\ \</sup>mbox{\footnotements}$  . All specifications are subject to change without notice.



2 of 3 Creation Date : November 15, 2021 (GMT)

RoHS Reach Pb Free

特性图表(这是参考数据,并不保证产品的特性。)


<sup>!</sup> Images are for reference only and show exemplary products.


<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.


 $<sup>!\ \</sup>mbox{\em All}$  specifications are subject to change without notice.

RoHS Reach Pb Free

## Associated Images







<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.