RoHS Reach Halogen Free Pb Free



ACM4520V-421-2P-T00

用途	车载等级
特点	Wire Wound 经线 AEC-Q200 AEC-Q200 Power 电源线
系列	ACM
状态	量产体制
品牌	TDK



	尺寸
长度(L)	$4.70 \text{mm} \pm 0.20 \text{mm}$
宽度(W)	4.50mm ±0.20mm
厚度 高低	2.00mm Max.

电气特性		
共模阻抗 [Typ.]	420Ω at 100MHz	
共模阻抗 [Min.]	300Ω at $100 MHz$	
共模电感	1.1µH at 1MHz (参考)	
额定电流	1. 4A	
额定电压	50VDC	
绝缘电阻 [Min.]	10ΜΩ	
直流电阻	55mΩ Max.	

	其他
使用温度范围	-40∼125° C
焊接方法	回流
异 按月伝	烙铁焊接
AEC-Q200	YES
包装形式	塑封编带 (180mm卷筒、带宽 12mm)
包装个数	800pcs
重量	0. 138g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free




特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{\ensuremath{\mbox{\textbf{l}}}} \ \mbox{\ensuremath{\mbox{\textbf{s}}}} \ \mbox{\ensuremath{\mbox{\textbf{c}}}} \$

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.