

ACM7060-701-2PL-TL01

RoHS Reach Halogen Free Pb Free

用途	一般等级
特点	Wire Wound <mark>绕线 Power</mark> 电源线
系列	ACM
状态	量产体制
品牌	TDK



	尺寸
长度(L)	7.00mm ± 0.20 mm
宽度(W)	6.00mm ±0.20mm
厚度 高低	3.50mm Max.

电	气特性
共模阻抗[Typ.]	700Ω at 100MHz
共模阻抗 [Min.]	500Ω at 100MHz
共模电感	1.5 μ H at 1MHz (参考)
额定电流	4A
额定电压	80VDC
绝缘电阻 [Min.]	10ΜΩ
直流电阻	15mΩ Max.

-	其他
使用温度范围	-40∼85° C
焊接方法	回流 烙铁焊接
AEC-Q200	NO
包装形式	塑封编带 (330mm卷筒、带宽 16mm)
包装个数	1500pcs
重量	0.35g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free



ACM7060-701-2PL-TL01


特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.