RoHS Reach Halogen Free Pb Free



## ACP3225-501-2P-T000

用途	一般等级
特点	Wire Wound <mark>绕线 Power</mark> 电源线
系列	ACP
状态	量产体制
品牌	TDK



	尺寸
长度(L)	3.20mm ±0.20mm
宽度(W)	2.50mm ±0.20mm
厚度   高低	1.90mm ±0.10mm

电	气特性
共模阻抗 [Typ.]	$500\Omega$ at $100\text{MHz}$
共模阻抗 [Min.]	$375\Omega$ at $100\text{MHz}$
共模电感	1.7µH at 1MHz (参考)
额定电流	2A
额定电压	60VDC
绝缘电阻 [Min.]	10ΜΩ
直流电阻	100mΩ Max.

į	其他
使用温度范围	-40∼85° C
焊接方法	回流 烙铁焊接
AEC-Q200	NO
包装形式	塑封编带 (180mm卷筒、帯宽 8mm)
包装个数	1000pcs
重量	0.53g

<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free




特性图表(这是参考数据,并不保证产品的特性。)


<sup>!</sup> Images are for reference only and show exemplary products.


<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.

## Associated Images







<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.