ACT45B-510-2P-TL003

用途	车载等级
特点	Wire Wound <mark>绕线 AEC-Q200</mark> AEC-Q200
系列	ACT
状态	量产体制
品牌	TDK



	尺寸
长度(L)	4.50mm ± 0.20 mm
宽度(W)	3. 20mm ±0. 20mm
厚度 高低	2.80mm ±0.20mm

电气特性		
共模阻抗[Typ.]	$2.8 \mathrm{k}\Omega$ at $10 \mathrm{MHz}$	
共模阻抗 [Min.]	$1 k \Omega$ at $10 MHz$	
共模电感	51μH at 100kHz (参考)	
额定电流	200mA	
额定电压	50VDC	
绝缘电阻 [Min.]	10ΜΩ	
直流电阻	1000mΩ Max.	

į	其他
使用温度范围	-40∼150° C
焊接方法	回流 烙铁焊接
AEC-Q200	YES
包装形式	塑封编带 (330mm卷筒、帯宽 12mm)
包装个数	2500pcs
重量	0. 14g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{All specifications}$ are subject to change without notice.



2 of 3 Creation Date : November 15, 2021 (GMT)

RoHS Reach Pb Free

特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.


 $^{!\ \}mbox{\footnotements}$. All specifications are subject to change without notice.

ACT45B-510-2P-TL003

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.