贴片NTC热敏电阻(传感器)

B57232V5103H360 RoHS Reach Halogen Free Pb Free

用途	车载等级
	AEC-Q200 AEC-Q200
特点	ULUL认证
	150°C 150° C
型	B57232V5
状态	量产体制
品牌	EPCOS



Г	₹寸
L x W 尺寸	1.0mm x 0.5mm [EIA 0402]
厚度 高低	0.60mm Max.
其他详细信息	请参照规格书

	电气特性	
电阻 [at 25° C]	$10\mathrm{k}\Omega$	
电阻容差	±3%	
B常数 [25/50° C]	3380К	
B常数 [25/85° C]	3435K	
B常数 [25/100° C]	3455K	
B常数容差	$\pm1\%$	
最大电力 [at 25° C]	150mW	
允许工作电流 [at 25° C]	500 μ A	
热辐射常数 [at 25° C]	2. 5mW/° C 2. 5mW/K	
其他详细信息	请参照规格书	


	其他
最大工作温度	150° C
UL文件No.	E69802
AEC-Q200	YES
焊接方法	请参照文件(安装说明)
包装形式	请参照文件(封贴和包装)

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{All specifications}$ are subject to change without notice.

Associated Images



[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{\ensuremath{\mathsf{Ill}}}$ specifications are subject to change without notice.