## 贴片NTC热敏电阻(传感器)

## B57442V5472H062

RoHS Reach Halogen Free Pb Free

用途	车载等级
特点	AEC-Q200 AEC-Q200 UL UL认证 150°C 150° C
型	B57442V5
状态	量产体制
品牌	EPCOS



尺寸	
L x W 尺寸	2.0mm x 1.25mm [EIA 0805]
厚度   高低	1.30mm Max.
其他详细信息	请参照规格书

	电气特性
电阻 [at 25° C]	$4.7 \mathrm{k} \Omega$
电阻容差	± 3%
B常数 [25/50° C]	3590K
B常数 [25/85° C]	3635K
B常数 [25/100° C]	3650K
B常数容差	± 3%
最大电力 [at 25° C]	210mW
允许工作电流 [at 25° C]	10 µ A
热辐射常数 [at 25° C]	3.5mW/° C   3.5mW/K
其他详细信息	请参照规格书


	其他
最大工作温度	150° C
UL文件No.	E69802
AEC-Q200	YES
焊接方法	请参照文件(安装说明)
包装形式	请参照文件(封贴和包装)

<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.

## Associated Images



<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

 $<sup>!\ \</sup>mbox{\em All}$  specifications are subject to change without notice.