

NTC元件

B57550G1104G000

RoHS Reach Halogen Free

用途



一般等级

车载等级

特点

AEC-Q200

UL Certificate

Product Type

玻璃封装型 NTC热敏电阻

Terminal Shape

径向引线

型

G1550

状态



量产体制

品牌

EPCOS



尺寸

尺寸信息

[请参照规格书](#)

电气特性

Nominal Resistance	100k $\Omega$ at 25 $^{\circ}$ C
Nominal Resistance Tolerance	$\pm$ 2%
Nominal B value (Typ.) [25/100 $^{\circ}$ C]	4092K
Nominal B value Tolerance	$\pm$ 1%
Reference B value (Typ.) [25/85 $^{\circ}$ C]	4072K
Reference B value (Typ.) [0/100 $^{\circ}$ C]	
最大电力 [at 25 $^{\circ}$ C]	32mW
热辐射常数 [at 25 $^{\circ}$ C]	750 $\mu$ W/ $^{\circ}$ C

其他

使用温度范围	-55~300 $^{\circ}$ C
Terminal Note	Dumet wire (copper-clad FeNi)_Option: Nickel plating
UL文件No.	E69802
AEC-Q200	YES
包装形式	

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.