B64290L0048X087 RoHS Pb Free

磁芯形状	环形磁心(环形磁心)
特点	General For general purpose
材料名称	Mn-Zn
铁氧体材料	N87
状态	量产体制



	尺寸
Size (IEC 62317) AxBxC	R 34/20.5/12.5
其他详细信息	

电	气特性
Core Factor	0. 99mm ⁻¹
Effective Cross-Sectional Area	82. 6mm²
Effective Magnetic Path Length	82. 06mm
Effective Core Volume	6778mm³
AL Value / (nH / N²)	2790 ±25%
铁心损耗 / (W / set) [Max.]	4.2 (200mT, 100kHz, 100° C)
Air Gap	O mm
重量	33g

电气特性(材料)		
初始磁导率 μi	2200 Nom.	
饱和磁通密度 Bs / mT	390 (100° C)	
居里温度 Tc [Min.]	210° C	
铁心损耗 / (kW / m³) [Max.]	375	


[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{All specifications}$ are subject to change without notice.

 $290\mathsf{L}0048\mathsf{X}087$ RoHS Pb Free

Associated Images



[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.