


B65857A0063A066 RoHS Pb Free

磁芯形状	EP (EPX)
特点	Telecom For Telecommunication
材料名称	Mn-Zn
铁氧体材料	T66
状态	量产体制



	尺寸
Size (IEC 62317) AxBxC	EPX 7/9
	<u>请参照规格书</u>

电气特性			
Core Factor	0. 91mm <sup>-1</sup>		
Effective Cross-Sectional Area	17. 2mm²		
Effective Magnetic Path Length	15.7mm		
Effective Core Volume	270mm³		
AL Value / (nH / N²)	63 ±3%		
铁心损耗 / (W / set) [Max.]			
Air Gap	0.35mm Nom.		
重量	2. 8g		

	电气特性(材料)	
初始磁导率 μί	13000 Nom.	
饱和磁通密度 Bs / mT	360 (25° C)	
居里温度 Tc [Min.]	100° C	
铁心损耗 / (kW / m³) [Max.]		


<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

 $<sup>! \ \</sup>mbox{All specifications}$  are subject to change without notice.

B65857A0063A066 RoHS Pb Free

## Associated Images



<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

 $<sup>!\ \</sup>mbox{\em All}$  specifications are subject to change without notice.