B66317G0250X187 RoHS Pb Free

磁芯形状	E (EE)
特点	General For general purpose
材料名称	Mn-Zn
铁氧体材料	N87
状态	量产体制



	尺寸
Size (IEC 62317) AxBxC	E 25/13/7
	<u>请参照规格书</u>

电气特性		
Core Factor	1. 1mm <sup>-1</sup>	
Effective Cross-Sectional Area	52. 5mm²	
Effective Magnetic Path Length	57.5mm	
Effective Core Volume	3020mm³	
AL Value / (nH / N²)	250 Nom.	
铁心损耗 / (W / set) [Max.]		
Air Gap	0.25mm ±0.02mm	
重量	16g	

电气特性(材料)		
初始磁导率 μi	2200 Nom.	
饱和磁通密度 Bs / mT	390 (100° C)	
居里温度 Tc [Min.]	210° C	
铁心损耗 / (kW / m³) [Max.]	375	


<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

 $<sup>! \ \</sup>mbox{All specifications}$  are subject to change without notice.

B66317G0250X187 RoHS Pb Free

## Associated Images



<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

 $<sup>!\ \</sup>mbox{\em All}$  specifications are subject to change without notice.