

B82422H1152K008 RoHS Reach Halogen Free Pb Free

用途	车载等级
特点	AEC-Q200 AEC-Q200
	No Directivity 无方向性 Wire Wound
	Wire Wound
系列   型	В82422Н
状态	量产体制
品牌	EPCOS




	n.t.	
	尺寸	
长度(L)	$3.20$ mm $\pm 0.20$ mm	
宽度 (W)	$2.50$ mm $\pm 0.20$ mm	
厚度   高低	$2.20$ mm $\pm 0.20$ mm	
推荐焊盘布局(A)	2.70mm Nom.	
推荐焊盘布局(B)	1.15mm Nom.	
推荐焊盘布局(C)	2.10mm Nom.	


电气特性		
电感	$1.5\muH~\pm10\%$ at $7.96 MHz$	
额定电流(基于L变化) [Typ.]	1.52A (30% Down)	
额定电流(基于L变化) [Min.]	1. 375A (30% Down)	
额定电流(基于温度上升) [Typ.]	960mA (45° C Rise)	
额定电流(基于温度上升) [Min.]		
直流电阻 [Typ.]		
直流电阻 [Max.]	$130$ m $\Omega$	
自我共振频率 [Min.]	110MHz	
自我共振频率 [Typ.]		
Q [Min.]	8 at 7.96MHz	
Q [Typ.]		

į	其他
使用温度范围(包括自我温度上升)	-55∼150° C
焊接方法	回流
AEC-Q200	YES
包装形式	塑封编带 (330mm卷筒、带宽 8mm)
包装个数	7500pcs
重量	Approx. 0.05g

- ! Images are for reference only and show exemplary products.
- ! This PDF document was created based on the data listed on the TDK Corporation website.
- ! All specifications are subject to change without notice.

## Associated Images





<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

 $<sup>!\ \</sup>mbox{\em All}$  specifications are subject to change without notice.