RoHS Reach Halogen Free Pb Free



B82432C1563J000

用途	车载等级	
	AEC-Q200 AEC-Q200	
特点	No Directivity 无方向性	
	Wire Wound 绕线	
	Ferrite Core 铁氧体磁芯	
系列 型	B82432C	
状态	量产体制	
品牌	EPCOS	



	尺寸	
长度(L)	4.50 mm ± 0.20 mm	
宽度(W)	3.20mm ±0.20mm	
厚度 高低	3. 20mm ±0. 20mm	
推荐焊盘布局(A)	3. 60mm Nom.	
推荐焊盘布局(B)	1.30mm Nom.	
推荐焊盘布局(C)	3. 20mm Nom.	

电气特性		
电感	$56\mu\mathrm{H}~\pm5\%$ at $100\mathrm{kHz}$	
额定电流	200mA	
直流电阻 [Typ.]		
直流电阻 [Max.]	2. 5 Ω	
自我共振频率 [Min.]	11MHz	
自我共振频率[Typ.]		
Q [Min.]	30 at 2.52MHz	
Q [Typ.]		


į	其他
使用温度范围(包括自我温度上升)	-55∼150° C
焊接方法	回流
AEC-Q200	YES
包装形式	塑封编带 (330mm卷筒、帯宽 12mm)
包装个数	2500pcs
重量	Approx. 0.13g


[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images





[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.