
## 积层贴片陶瓷片式电容器

## C0402CH1C470J020BC

RoHS Reach Halogen Free Pb Free

交货型号	C0402CH1C470JT****	
用途	一般等级	
特点	General 一般(~75V)	
系列	CO402 [EIA 01005]	
状态	↑ 量产体制(新设计非推荐) 推荐代替型号 : C0402C0G1C470J020BC (不保证其兼容性。)	



尺寸	
长度(L)	0.40mm ±0.02mm
宽度(W)	0.20mm ±0.02mm
厚度(T)	0.20mm ±0.02mm
端子宽度(B)	0.07mm Min.
端子间隔(G)	0.14mm Min.
推荐焊盘布局 (PA)	0.15mm to 0.25mm
推荐焊盘布局(PB)	0.15mm to 0.25mm
推荐焊盘布局(PC)	0.15mm to 0.25mm

电气特性		
电容	47pF ±5%	
额定电压	16VDC	
温度特性	CH(0±60ppm/° C)	
Q (Min.)	1000	
绝缘电阻 (Min.)	10000M Ω	


	其他
焊接方法	回流
AEC-Q200	NO
包裝形式	纸编带 (180mm卷筒)
包装个数	20000pcs

<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

 $<sup>! \ \</sup>mbox{All specifications}$  are subject to change without notice.

RoHS Reach Halogen Free Pb Free





特性图表(这是参考数据,并不保证产品的特性。)


<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free

## Associated Images



<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.