积层贴片陶瓷片式电容器

C0402JB0G152K020BC

RoHS Reach Halogen Free Pb Free

交货型号	C0402JB0G152KT****
用途	一般等级
特点	General 一般 (～75V)
系列	C0402 [EIA 01005]
状态	量产体制(新设计非推荐)



尺寸	
长度(L)	0.40mm ±0.02mm
宽度(W)	0.20mm ±0.02mm
厚度(T)	0.20mm ±0.02mm
端子宽度(B)	0.07mm Min.
端子间隔(G)	0.14mm Min.
推荐焊盘布局(PA)	0.15mm to 0.25mm
推荐焊盘布局(PB)	0.15mm to 0.25mm
推荐焊盘布局(PC)	0.15mm to 0.25mm

电气特性	
电容	1.5nF ±10%
额定电压	4VDC
温度特性	JB(±10%)
耗散因数 (Max.)	5%
绝缘电阻 (Min.)	10000MΩ

其他	
焊接方法	回流
AEC-Q200	NO
包装形式	纸编带 (180mm卷筒)
包装个数	20000pcs

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.

特性图表(这是参考数据，并不保证产品的特性。)

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.

Associated Images

Land Pattern (Terminal Connection)

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.