
## C0603CH1E100D030BA

RoHS Reach Halogen Free Pb Free

交货型号	C0603CH1E100DT****	
用途	一般等级	
特点	General 一般(~75V)	
系列	C0603 [EIA 0201]	
状态	↑ 量产体制(新设计非推荐) 推荐代替型号 : <u>C0603C0G1E100D030BA</u> (不保证其兼容性。)	



,	₹₫
长度(L)	$0.60 \text{mm} \pm 0.03 \text{mm}$
宽度(W)	0.30mm ±0.03mm
厚度(T)	0.30mm ±0.03mm
端子宽度(B)	0.10mm Min.
端子间隔(G)	0.20mm Min.
推荐焊盘布局(PA)	0.25mm to 0.35mm
推荐焊盘布局(PB)	0.20mm to 0.30mm
推荐焊盘布局(PC)	0.25mm to 0.35mm

电气特性	
电容	$10 \mathrm{pF} \pm 0.5 \mathrm{pF}$
额定电压	25VDC
温度特性	CH(0±60ppm/° C)
Q (Min.)	600
	10000MΩ

	其他
焊接方法	回流
AEC-Q200	NO
包裝形式	纸编带 (180mm卷筒)
包装个数	15000pcs

<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free



特性图表(这是参考数据,并不保证产品的特性。)


<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free

## Associated Images



<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

 $<sup>!\ \</sup>mbox{\footnotements}$  . All specifications are subject to change without notice.