
积层贴片陶瓷片式电容器

C0603CH1E150K030BA

RoHS Reach Halogen Free Pb Free

交货型号	C0603CH1E150KT****
用途	一般等级
特点	General 一般(~75V)
系列	C0603 [EIA 0201]
状态	▲ 量产体制(新设计非推荐)



,	₹ 7
长度(L)	0.60mm ±0.03mm
宽度(W)	$0.30 \text{mm} \pm 0.03 \text{mm}$
厚度(T)	0.30mm ±0.03mm
端子宽度(B)	0.10mm Min.
端子间隔(G)	0.20mm Min.
推荐焊盘布局(PA)	0.25mm to 0.35mm
推荐焊盘布局(PB)	0.20mm to 0.30mm
推荐焊盘布局(PC)	0.25mm to 0.35mm

电气特性		
电容	15pF ±10%	
额定电压	25VDC	
温度特性	CH(0±60ppm/° C)	
Q (Min.)	700	
绝缘电阻 (Min.)	10000MΩ	

	其他
焊接方法	回流
AEC-Q200	NO
包装形式	纸编带 (180mm卷筒)
包装个数	15000pcs

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{All specifications}$ are subject to change without notice.

RoHS Reach Halogen Free Pb Free



特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free

Associated Images



[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.