
积层贴片陶瓷片式电容器

C1005C0G1H151J050BE

RoHS Reach Halogen Free Pb Free

交货型号	C1005C0G1H151JT***S
用途	一般等级 车载用途时为 <u>CGA2B2C0G1H151J050BE</u> 。
特点	Soft 树脂电极品
系列	C1005 [EIA 0402]
状态	▲ 量产体制(新设计非推荐)



尺寸	
长度(L)	1.00mm +0.15, -0.05mm
宽度(W)	0.50mm +0.10, -0.05mm
厚度(T)	0.50mm +0.10, -0.05mm
端子宽度(B)	0.10mm Min.
端子间隔(G)	0.30mm Min.
推荐焊盘布局(PA)	0.30mm to 0.50mm
推荐焊盘布局(PB)	0.35mm to 0.45mm
推荐焊盘布局(PC)	0.40mm to 0.60mm

电气特性	
电容	$150 \mathrm{pF} \pm 5\%$
额定电压	50VDC
温度特性	$COG(0\pm30ppm/^{\circ} C)$
Q (Min.)	1000
	10000M Ω

	其他
焊接方法	回流
AEC-Q200	NO
包裝形式	纸编带 (180mm卷筒)
包装个数	10000pcs

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free



特性图表(这是参考数据,并不保证产品的特性。)

[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free



Associated Images



[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.