
积层贴片陶瓷片式电容器

C1005NP01H681J050BA

RoHS Reach Halogen Free Pb Free

交货型号	C1005NP01H681JT****
用途	一般等级 车载用途时为 <u>CGA2B2NP01H681J050BA</u> 。
特点	150°C 高温保证用
系列	C1005 [EIA 0402]
状态	量产体制



尺寸	
长度(L)	1.00mm ±0.05mm
宽度(W)	0.50mm ±0.05mm
厚度(T)	0.50mm ±0.05mm
端子宽度(B)	0.10mm Min.
端子间隔(G)	0.30mm Min.
推荐焊盘布局(PA)	0.30mm to 0.50mm
推荐焊盘布局(PB)	0.35mm to 0.45mm
推荐焊盘布局(PC)	0.40mm to 0.60mm

······································	气特性
电容	680pF ±5%
额定电压	50VDC
温度特性	NPO (0±30ppm/° C)
Q (Min.)	1000
绝缘电阻 (Min.)	10000M Ω

	其他
焊接方法	回流
AEC-Q200	NO
包裝形式	纸编带 (180mm卷筒)
包装个数	10000pcs

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free



特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free

Associated Images



[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.