
## 积层贴片陶瓷片式电容器

## C1005NP01H821J050BA

RoHS Reach Halogen Free Pb Free

交货型号	C1005NP01H821JT****	
用途	一般等级 车载用途时为 <u>CGA2B2NP01H821J050BA</u> 。	
特点	150°C 高温保证用	
系列	C1005 [EIA 0402]	
状态	▲ 量产体制(新设计非推荐)	



尺寸		
长度(L)	1.00mm ±0.05mm	
宽度(W)	0.50mm ±0.05mm	
厚度(T)	0.50mm ±0.05mm	
端子宽度(B)	0.10mm Min.	
端子间隔(G)	0.30mm Min.	
推荐焊盘布局 (PA)	0.30mm to 0.50mm	
推荐焊盘布局 (PB)	0.35mm to 0.45mm	
推荐焊盘布局(PC)	0.40mm to 0.60mm	

电气特性	
电容	820pF ±5%
额定电压	50VDC
温度特性	NPO (0±30ppm/° C)
Q (Min.)	1000
	10000M Ω

其他	
焊接方法	回流
AEC-Q200	NO
包装形式	纸编带 (180mm卷筒)
包装个数	10000pcs

<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free



特性图表(这是参考数据,并不保证产品的特性。)

<sup>!</sup> Images are for reference only and show exemplary products.


<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free



## Associated Images



<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.