## 

RoHS Reach Halogen Free Pb Free

交货型号	C1005X6S0G335MT****	$\sim$
用途	一般等级	
特点	General 一般 (~75V)	
系列	C1005 [EIA 0402]	6
状态	▲ 量产体制(新设计非推荐)	B

	尺寸
长度(L)	1.00mm ±0.10mm
宽度(W)	0.50mm ±0.10mm
厚度(T)	0.50mm ±0.10mm
端子宽度(B)	0.10mm Min.
端子间隔(G)	0.30mm Min.
推荐焊盘布局(PA)	0.30mm to 0.50mm
	0.35mm to 0.45mm
推荐焊盘布局(PC)	0.40mm to 0.60mm

电	气特性
电容	3.3 μF ±20%
额定电压	4VDC
	X6S (±22%)
	10%
	30M Ω

	其他
焊接方法	回流
AEC-Q200	NO
包装形式	纸编带(180mm卷筒)
包装个数	10000pcs

 $!\ \mbox{Images}$  are for reference only and show exemplary products.

 $!\ \mbox{This PDF}$  document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.

RoHS Reach Halogen Free Pb Free

特性图表(这是参考数据,并不保证产品的特性。)


! Images are for reference only and show exemplary products.

 $!\ \mbox{This PDF}$  document was created based on the data listed on the TDK Corporation website.

 $! \ \mbox{All specifications}$  are subject to change without notice.

RoHS Reach Halogen Free Pb Free

## Associated Images



 $!\ \mbox{Images}$  are for reference only and show exemplary products.

 $!\ \mbox{This PDF}$  document was created based on the data listed on the TDK Corporation website.

 $! \ \mbox{All specifications}$  are subject to change without notice.