


# 积层贴片陶瓷片式电容器

C1608CH2E221J080AA

RoHS Reach Halogen Free Pb Free

|      |   |
|------|---|
| 交货型号 | C1608CH2E221JT****  |
| 用途   | 一般等级  |
| 特点   | 中耐压 (100~630V)  |
| 系列   | C1608 [EIA 0603]  |
| 状态   | 量产体制(新设计非推荐)<br>推荐代替型号 : <a href="#">C1608COG2E221J080AA</a> (不保证其兼容性。) |



## 尺寸

|            |  |
|------------|--|
| 长度(L)      | 1.60mm ±0.10mm   |
| 宽度(W)      | 0.80mm ±0.10mm   |
| 厚度(T)      | 0.80mm ±0.10mm   |
| 端子宽度(B)    | 0.20mm Min.  |
| 端子间隔(G)    | 0.30mm Min.  |
| 推荐焊盘布局(PA) | 0.70mm to 1.00mm(Flow Soldering)<br>0.60mm to 0.80mm(Reflow Soldering) |
| 推荐焊盘布局(PB) | 0.80mm to 1.00mm(Flow Soldering)<br>0.60mm to 0.80mm(Reflow Soldering) |
| 推荐焊盘布局(PC) | 0.60mm to 0.80mm(Flow Soldering)<br>0.60mm to 0.80mm(Reflow Soldering) |

## 电气特性

|             |                 |
|-------------|-----------------|
| 电容          | 220pF ±5%       |
| 额定电压        | 250VDC          |
| 温度特性        | CH(0±60ppm/° C) |
| Q (Min.)    | 1000            |
| 绝缘电阻 (Min.) | 10000MΩ         |

## 其他

|          |               |
|----------|---------------|
| 焊接方法     | 流体<br>回流      |
| AEC-Q200 | NO            |
| 包装形式     | 纸编带 (180mm卷筒) |
| 包装个数     | 4000pcs       |

特性图表 (这是参考数据，并不保证产品的特性。)

## Associated Images

