


# 积层贴片陶瓷片式电容器

C2012CH2W561J060AA

RoHS Reach Halogen Free Pb Free

|      |                    |
|------|--------------------|
| 交货型号 | C2012CH2W561JT**** |
| 用途   | 一般等级               |
| 特点   | 中耐压 (100~630V)     |
| 系列   | C2012 [EIA 0805]   |
| 状态   | 量产体制(新设计非推荐)       |



## 尺寸

|            |  |
|------------|--|
| 长度(L)      | 2.00mm ±0.20mm   |
| 宽度(W)      | 1.25mm ±0.20mm   |
| 厚度(T)      | 0.60mm ±0.15mm   |
| 端子宽度(B)    | 0.20mm Min.  |
| 端子间隔(G)    | 0.50mm Min.  |
| 推荐焊盘布局(PA) | 1.00mm to 1.30mm(Flow Soldering)<br>0.90mm to 1.20mm(Reflow Soldering) |
| 推荐焊盘布局(PB) | 1.00mm to 1.20mm(Flow Soldering)<br>0.70mm to 0.90mm(Reflow Soldering) |
| 推荐焊盘布局(PC) | 0.80mm to 1.10mm(Flow Soldering)<br>0.90mm to 1.20mm(Reflow Soldering) |

## 电气特性

|             |                 |
|-------------|-----------------|
| 电容          | 560pF ±5%       |
| 额定电压        | 450VDC          |
| 温度特性        | CH(0±60ppm/° C) |
| Q (Min.)    | 1000            |
| 绝缘电阻 (Min.) | 10000M Ω        |

## 其他

|          |               |
|----------|---------------|
| 焊接方法     | 流体<br>回流      |
| AEC-Q200 | NO            |
| 包装形式     | 纸编带 (180mm卷筒) |
| 包装个数     | 4000pcs       |

特性图表 (这是参考数据，并不保证产品的特性。)

## Associated Images

