





| | | |
|------|---|----------------|
| 交货型号 | C3216CH2J822JT**** | |
| 用途 |  | 一般等级 |
| 特点 |  | 中耐压 (100~630V) |
| 系列 | C3216 [EIA 1206] | |
| 状态 |  | 量产体制(新设计非推荐) |



| 尺寸 | |
|-------------|-------------------------------------|
| 长度(L) | 3.20mm ±0.20mm |
| 宽度(W) | 1.60mm ±0.20mm |
| 厚度(T) | 1.60mm ±0.20mm |
| 端子宽度(B) | 0.20mm Min. |
| 端子间隔(G) | 1.00mm Min. |
| 推荐焊盘布局 (PA) | 2.10mm to 2.50mm (Flow Soldering) |
| | 2.00mm to 2.40mm (Reflow Soldering) |
| 推荐焊盘布局 (PB) | 1.10mm to 1.30mm (Flow Soldering) |
| | 1.00mm to 1.20mm (Reflow Soldering) |
| 推荐焊盘布局 (PC) | 1.00mm to 1.30mm (Flow Soldering) |
| | 1.10mm to 1.60mm (Reflow Soldering) |

| 电气特性 | |
|-------------|------------------|
| 电容 | 8.2nF ±5% |
| 额定电压 | 630VDC |
| 温度特性 | CH (0±60ppm/° C) |
| Q (Min.) | 1000 |
| 绝缘电阻 (Min.) | 10000MΩ |

| 其他 | |
|----------|----------------|
| 焊接方法 | 流体 |
| | 回流 |
| AEC-Q200 | NO |
| 包装形式 | 塑封编带 (180mm卷筒) |
| 包装个数 | 2000pcs |

特性图表 (这是参考数据，并不保证产品的特性。)

Associated Images

