


| | |
|------|--|
| 交货型号 | C3216X5R1H475KT**** |
| 用途 | 一般等级 车载用途时为 CGA5L3X5R1H475K160AB 。 |
| 特点 | General 一般 (~75V) |
| 系列 | C3216 [EIA 1206] |
| 状态 | 量产体制(新设计非推荐) 推荐代替型号： C3216X7R1H475K160AC (不保证其兼容性。) |



尺寸

| | |
|------------|--|
| 长度(L) | 3.20mm ±0.20mm |
| 宽度(W) | 1.60mm ±0.20mm |
| 厚度(T) | 0.85mm ±0.15mm |
| 端子宽度(B) | 0.20mm Min. |
| 端子间隔(G) | 1.00mm Min. |
| 推荐焊盘布局(PA) | 2.10mm to 2.50mm(Flow Soldering) 2.00mm to 2.40mm(Reflow Soldering) |
| 推荐焊盘布局(PB) | 1.10mm to 1.30mm(Flow Soldering) 1.00mm to 1.20mm(Reflow Soldering) |
| 推荐焊盘布局(PC) | 1.00mm to 1.30mm(Flow Soldering) 1.10mm to 1.60mm(Reflow Soldering) |

电气特性

| | |
|-------------|-------------|
| 电容 | 4.7 μF ±10% |
| 额定电压 | 50VDC |
| 温度特性 | X5R(±15%) |
| 耗散因数 (Max.) | 5% |
| 绝缘电阻 (Min.) | 106MΩ |

其他

| | |
|----------|---------------|
| 焊接方法 | 流体 回流 |
| AEC-Q200 | NO |
| 包装形式 | 纸编带 (180mm卷筒) |
| 包装个数 | 4000pcs |

特性图表 (这是参考数据，并不保证产品的特性。)

Associated Images

