


积层贴片陶瓷片式电容器

C3216X7S0G476M160AB

RoHS Reach Halogen Free Pb Free

| | |
|------|--------------------------|
| 交货型号 | C3216X7S0G476MT**** |
| 用途 | 一般等级 |
| 特点 | General 一般 (~75V) |
| 系列 | C3216 [EIA 1206] |
| 状态 | 量产体制 |



尺寸

| | |
|-------------|--|
| 长度(L) | 3.20mm ±0.20mm |
| 宽度(W) | 1.60mm ±0.20mm |
| 厚度(T) | 1.60mm ±0.20mm |
| 端子宽度(B) | 0.20mm Min. |
| 端子间隔(G) | 1.00mm Min. |
| 推荐焊盘布局 (PA) | 2.10mm to 2.50mm (Flow Soldering) 2.00mm to 2.40mm (Reflow Soldering) |
| 推荐焊盘布局 (PB) | 1.10mm to 1.30mm (Flow Soldering) 1.00mm to 1.20mm (Reflow Soldering) |
| 推荐焊盘布局 (PC) | 1.00mm to 1.30mm (Flow Soldering) 1.10mm to 1.60mm (Reflow Soldering) |

电气特性

| | |
|-------------|------------|
| 电容 | 47 μF ±20% |
| 额定电压 | 4VDC |
| 温度特性 | X7S (±22%) |
| 耗散因数 (Max.) | 10% |
| 绝缘电阻 (Min.) | 2MΩ |

其他

| | |
|----------|----------------|
| 焊接方法 | 流体 回流 |
| AEC-Q200 | NO |
| 包装形式 | 塑封编带 (180mm卷筒) |
| 包装个数 | 2000pcs |

特性图表 (这是参考数据，并不保证产品的特性。)

Associated Images

