
## 积层贴片陶瓷片式电容器

CAA572C0G3A303J640LH

RoHS Reach Halogen Free Pb Free

交货型号	CAA572C0G3A303JT****
用途	一般等级
	High <mark>高耐压(1000V以上)</mark>
特点	MEGA I 金属支架电容(横向排列型)
	LowR
系列	CAA572(5750) [EIA 2220]
状态	量产体制



	尺寸
长度(L)	6.00mm ±0.50mm
宽度(W)	5.60mm ±0.50mm
厚度(T)	6.40mm ±0.50mm
金属端子宽度(E)	1.20mm ±0.20mm
推荐焊盘布局(PA)	4.30mm to 4.70mm
推荐焊盘布局(PB)	1.50mm to 2.00mm
推荐焊盘布局(PC)	5.20mm to 5.70mm

电气特性		
电容	30nF ±5%	
额定电压	1kVDC	
温度特性	COG(0±30ppm/° C)	
Q (Min.)	1000	
绝缘电阻(Min.)	10000M Ω	

其他	
焊接方法	回流
AEC-Q200	NO
包装形式	塑封编带 (330mm卷筒)
包装个数	400pcs

<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free

CAA572C0G3A303J640LH

特性图表(这是参考数据,并不保证产品的特性。)

<sup>!</sup> Images are for reference only and show exemplary products.


<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free



## Associated Images



<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.