


积层贴片陶瓷片式电容器

CGA9N4X7R2J224K230KE

RoHS Reach Halogen Free Pb Free

交货型号	CGA9N4X7R2J224KT***S
用途	车载等级
特点	AEC-Q200
	中耐压 (100~630V)
	树脂电极品
系列	CGA9 (5750) [EIA 2220]
状态	量产体制



尺寸

长度(L)	5.70mm +0.50, -0.40mm
宽度(W)	5.00mm ±0.40mm
厚度(T)	2.30mm +0.30, -0.20mm
端子宽度(B)	0.20mm Min.
端子间隔(G)	
推荐焊盘布局 (PA)	4.10mm to 4.80mm
推荐焊盘布局 (PB)	1.20mm to 1.40mm
推荐焊盘布局 (PC)	4.00mm to 5.00mm

电气特性

电容	220nF ±10%
额定电压	630VDC
温度特性	X7R (±15%)
耗散因数 (Max.)	3%
绝缘电阻 (Min.)	2272MΩ

其他

焊接方法	回流
AEC-Q200	YES
包装形式	塑封编带 (180mm卷筒)
包装个数	500pcs

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

特性图表 (这是参考数据，并不保证产品的特性。)

Associated Images

