


KPZ1608SHR102ATD25

RoHS Reach Halogen Free Pb Free

用途	车载等级
特点	AEC-Q200 Power 电源用
	Soft
系列	KPZ-HR
状态	量产体制



	尺寸
长度(L)	1.60mm ±0.15mm
宽度(W)	0.80mm ±0.15mm
厚度(T)	0.80mm ±0.15mm
推荐焊盘布局(A)	0.60mm Nom.
推荐焊盘布局(B)	0.80mm Nom.
推荐焊盘布局(C)	0.80mm Nom.

	电气特性	
阻抗 at 100MHz	$1 \mathrm{k} \Omega \pm 25\%$	
额定电流	800mA	
直流电阻(Max.)	300mΩ	

其他			
使用温度范围(包括自我温度上升)	-55~150° C		
焊接方法	回流		
件按刀伝	烙铁焊接		
AEC-Q200	YES		
包装形式	纸编带 (180mm卷筒、带宽 8mm)		
包装个数	4000pcs		
重量	0. 004g		

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



, ,

RoHS Reach Halogen Free Pb Free



特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



Associated Images



[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{!\ \}mbox{\footnotements}$. All specifications are subject to change without notice.