RoHS Reach Halogen Free Pb Free



MCZ0605AH900SDT000

用途	一般等级
特点	Multilayer 积层 High-speed 高速信号线
系列	MCZ
状态	▲ 量产体制(新设计非推荐) 推荐代替型号 : 无
品牌	TDK



	尺寸
长度(L)	$0.65 \text{mm} \pm 0.05 \text{mm}$
宽度(W)	0.50mm ±0.05mm
厚度 高低	0.30mm ±0.05mm

电气特性		
共模阻抗 [Typ.]	90Ω at $100 MHz$	
共模阻抗 [Min.]		
共模电感	157nH at 1MHz (参考)	
额定电流	100mA	
额定电压	5VDC	
	10ΜΩ	
直流电阻	3.9Ω Max.	

	其他
使用温度范围	-40∼85° C
焊接方法	回流
冲按 力 <i>伝</i>	烙铁焊接
AEC-Q200	NO
包装形式	纸编带 (180mm卷筒、带宽 8mm)
包装个数	10000pcs
重量	0. 0006g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free



特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



Associated Images



[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{!\ \}mbox{\footnotements}$. All specifications are subject to change without notice.