RoHS Reach Halogen Free Pb Free



MCZ0806AH220L2TA0G

用途	一般等级
特点	Multilayer <mark>积层</mark> High-speed 高速信号线
系列	MCZ
状态	↑ 量产体制(新设计非推荐) 推荐代替型号 : 无
品牌	TDK



	尺寸
长度(L)	$0.85 \mathrm{mm}~\pm 0.05 \mathrm{mm}$
宽度(W)	0.65mm ±0.05mm
厚度 高低	0.45mm ±0.05mm

电气特性	
共模阻抗[Typ.]	22Ω at 100MHz
共模阻抗 [Min.]	
共模电感	39nH at 1MHz (参考)
额定电流	100mA
额定电压	5VDC
	10ΜΩ
直流电阻	1.5Ω Max.

	其他
使用温度范围	-40∼85° C
焊接方法	回流
冲按 力 <i>伝</i>	烙铁焊接
AEC-Q200	NO
包装形式	塑封编带 (180mm卷筒、带宽 8mm)
包装个数	10000pcs
重量	0. 0014g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free




特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.