
RoHS Reach Halogen Free Pb Free



## $\tt MCZ1210AH301L2TAOG$

用途	一般等级
特点	Multilayer 积层 High-speed 高速信号线
系列	MCZ
状态	量产体制
品牌	TDK



	尺寸
长度(L)	$1.25 \text{mm} \pm 0.15 \text{mm}$
宽度(W)	1.00mm $\pm 0.15$ mm
厚度   高低	0.50mm ±0.10mm

电气特性		
共模阻抗 [Typ.]	$300\Omega$ at $100\text{MHz}$	
共模阻抗 [Min.]		
共模电感	523nH at 1MHz (参考)	
额定电流	100mA	
额定电压	5VDC	
绝缘电阻 [Min.]	10ΜΩ	
直流电阻	4.5Ω Max.	

:	其他
使用温度范围	-40∼85° C
焊接方法	回流
件技力仏	烙铁焊接
AEC-Q200	NO
包装形式	塑封编带 (180mm卷筒、带宽 8mm)
包装个数	4000pcs
重量	0.003g

<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free



特性图表(这是参考数据,并不保证产品的特性。)


<sup>!</sup> Images are for reference only and show exemplary products.


<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.


 $<sup>! \ \</sup>mbox{\ensuremath{\mbox{\textbf{.}}}}$  All specifications are subject to change without notice.



## Associated Images







<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.