
RoHS Reach Halogen Free Pb Free



MCZ1210AH360L2TA0G

用途	一般等级
特点	Multilayer <mark>积层</mark> High-speed 高速信号线
系列	MCZ
状态	量产体制
品牌	TDK



	尺寸
长度(L)	$1.25 \text{mm} \pm 0.15 \text{mm}$
宽度(W)	1.00mm ± 0.15 mm
厚度 高低	0.50mm ±0.10mm

电气特性	
共模阻抗[Typ.]	36Ω at $100 MHz$
共模阻抗 [Min.]	
共模电感	61nH at 1MHz (参考)
额定电流	200mA
额定电压	5VDC
绝缘电阻 [Min.]	10ΜΩ
直流电阻	1000mΩ Max.

;	其他
使用温度范围	-40∼85° C
焊接方法	回流 烙铁焊接
AEC-Q200	NO
包装形式	塑封编带 (180mm卷筒、带宽 8mm)
包装个数	4000pcs
重量	0.003g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free




特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.