


MEM2012SC220T001

RoHS Reach Halogen Free Pb Free

用途	一般等级
特点	Signal 信号线用
系列	МЕМ
状态	量产体制



	尺寸
长度(L)	2.00mm ±0.20mm
宽度(W)	1.25mm ± 0.20 mm
厚度(T)	0.80mm +0.15, -0.20mm

	电气特性	
插入损耗 [Typ.]	$10 dB (500 MHz \sim 2 GHz)$	
截止频率[Typ.]		
额定电压 [Max.]	12V	
额定电流 [Max.]	1A	
直流电阻(Max.)		
额定电容 [Typ.]	22pF	

į	其他
电路型	T Type
传输线路	单端
使用温度范围	-40∼85° C
焊接方法	回流
FT女刀仏	烙铁焊接
AEC-Q200	NO
包装形式	纸编带 (180mm卷筒)
包装个数	4000pcs
重量	0.008g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



(0.11)

RoHS Reach Halogen Free Pb Free




特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images







[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.