

用途	 车载等级
特点	 AEC-Q200
Product Type	玻璃封装型 NTC热敏电阻
Terminal Shape	径向引线 (轴向U型弯曲带涂层) 轴向引线
系列	NTCDZ
状态	 量产体制
品牌	TDK



尺寸	
长度 (L)	3.00mm +0.00, -0.70mm
Diameter (D)	2.30mm Max.
Terminal Length	16.00mm ±1.00mm
Terminal Diameter	0.45mm Max.

电气特性	
Nominal Resistance	5kΩ at 25° C
Nominal Resistance Tolerance	±3%
Reference Resistance	5kΩ at 25° C
Nominal B value (Typ.) [0/100° C]	4006K
Nominal B value Tolerance	±2%
Reference B value (Typ.) [25/85° C]	4000K
Reference B value (Typ.) [25/100° C]	3985K
最大电力 [at 25° C]	20mW
热辐射常数 [at 25° C]	2mW/° C

其他	
使用温度范围	-40~160° C
Terminal Note	Ni镀层
UL文件No.	
AEC-Q200	YES
包装形式	
包装个数	200pcs
重量	0.064g

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.