


贴片NTC热敏电阻(传感器)

NTCG104KF104HT1

RoHS Reach Halogen Free Pb Free

| | |
|----|----------------|
| 用途 | 一般等级 |
| 特点 | UL认证 125° C |
| 系列 | NTCG |
| 状态 | 量产体制 |
| 品牌 | TDK |



尺寸

| | |
|------------|----------------|
| 长度(L) | 1.00mm ±0.05mm |
| 宽度(W) | 0.50mm ±0.05mm |
| 厚度(T) | 0.50mm ±0.05mm |
| 端子宽度(B) | 0.10mm Min. |
| 推荐焊盘布局(PA) | 0.50mm ±0.10mm |
| 推荐焊盘布局(PB) | 0.50mm ±0.10mm |
| 推荐焊盘布局(PC) | 0.50mm ±0.10mm |

电气特性

| | |
|-----------------------|-----------------|
| 电阻 [at 25° C] | 100k Ω |
| 电阻容差 | ±3% |
| B常数(Typ.) [25/50° C] | 4419K |
| B常数(Typ.) [25/85° C] | 4485K |
| B常数(Typ.) [25/100° C] | 4508K |
| B常数容差 | ±1% |
| 最大电力 [at 25° C] | 100mW |
| 允许工作电流 [at 25° C] | 100 μA |
| 热辐射常数 [at 25° C] | 1mW/° C 1mW/K |

其他

| | |
|----------|---------------|
| 最大工作温度 | 125° C |
| 焊接方法 | 回流 |
| UL文件No. | E250289 |
| AEC-Q200 | NO |
| 包装形式 | 纸编带 (180mm卷筒) |
| 包装个数 | 10000pcs |
| 重量 | 0.0013g |

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

贴片NTC热敏电阻(传感器)

NTCG104KF104HT1

RoHS Reach Halogen Free Pb Free

Associated Images

