
贴片NTC热敏电阻(传感器)

NTCG204AH473JT1S

RoHS Reach Halogen Free Pb Free

用途	←载等级
特点	AEC-Q200 AEC-Q200 150°C 150° C
系列	NTCG
状态	量产体制
品牌	TDK



	尺寸
长度(L)	2.00mm ±0.20mm
宽度(W)	1. 25mm ±0. 20mm
厚度(T)	0.70mm ±0.20mm
端子宽度(B)	0.20mm Min.
推荐焊盘布局(PA)	1.05mm ±0.15mm
推荐焊盘布局(PB)	0.80mm ±0.10mm
推荐焊盘布局(PC)	1.05mm ±0.15mm

电4	气特性
电阻 [at 25° C]	47 k Ω
电阻容差	±5%
B常数(Typ.) [25/50° C]	3930K
B常数(Typ.) [25/85°C]	4000K
B常数(Typ.) [25/100° C]	4023K
B常数容差	±3%
最大电力 [at 25° C]	200mW
允许工作电流 [at 25° C]	440 μ Α
热辐射常数 [at 25° C]	2mW/° C 2mW/K


	其他
最大工作温度	125° C
焊接方法	回流
UL文件No.	E250289
AEC-Q200	YES
包装形式	纸编带 (180mm卷筒)
包装个数	2000pcs
重量	0.0072g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images



[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.