

# NTC元件

NTCGF3LG222HC5SB

RoHS Reach Pb Free

## 用途



一般等级

## 特点

**Product Type** 树脂涂层型 NTC热敏电阻

**Terminal Shape** 平行电线

**系列** NTCGF

## 状态



量产体制(新设计非推荐)

推荐代替型号 : 无

## 品牌

TDK



## 尺寸

长度(L)	6.00mm ±1.00mm
Diameter(D)	3.50mm ±0.50mm
Terminal Length	
Terminal Diameter	0.50mm ±0.10mm

## 电气特性

Nominal Resistance	6.204kΩ at 0° C
Nominal Resistance Tolerance	±3%
Reference Resistance	2.185kΩ at 25° C
Nominal B value (Typ.) [0/100° C]	3505K
Nominal B value Tolerance	±2%
Reference B value (Typ.) [25/85° C]	3535K
Reference B value (Typ.) [25/100° C]	3553K
最大电力 [at 25° C]	40mW
热辐射常数 [at 25° C]	4mW/° C

## 其他

使用温度范围	-40~125° C
Terminal Note	平行电线
UL文件No.	
AEC-Q200	NO
包装形式	散装 (袋子)
包装个数	500pcs
重量	0.197g

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.