


贴片NTC热敏电阻(传感器)

NTCSP104BF473FT1SX

RoHS Reach Halogen Free Pb Free

用途	车载等级
特点	AEC-Q200 AEC-Q200 150°C 150° C 导电性环氧树脂用
系列	NTCSP
状态	量产体制
品牌	TDK



尺寸

长度(L)	1.00mm ±0.05mm
宽度(W)	0.50mm ±0.05mm
厚度(T)	0.50mm ±0.05mm
端子宽度(B)	0.10mm Min.
推荐焊盘布局(PA)	0.65mm ±0.05mm
推荐焊盘布局(PB)	0.40mm ±0.05mm
推荐焊盘布局(PC)	0.60mm ±0.10mm

电气特性

电阻 [at 25° C]	47k Ω
电阻容差	±1%
B常数(Typ.) [25/50° C]	4050K
B常数(Typ.) [25/85° C]	4114K
B常数(Typ.) [25/100° C]	4137K
B常数容差	±1%
最大电力 [at 25° C]	125mW
允许工作电流 [at 25° C]	140 μ A
热辐射常数 [at 25° C]	1mW/° C 1mW/K

其他

最大工作温度	150° C
焊接方法	对应导电性环氧树脂
UL文件No.	
AEC-Q200	YES
包装形式	纸编带 (180mm卷筒)
包装个数	10000pcs
重量	0.0013g

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

贴片NTC热敏电阻(传感器)

NTCSP104BF473FT1SX

RoHS Reach Halogen Free Pb Free

Associated Images

