RoHS Reach Halogen Free Pb Free



SPM10040T-150M-HZ

用途	车载等级
	AEC-Q200 AEC-Q200
alde de	Wire Wound <mark>绕线</mark>
特点	Shield磁屏蔽
	Metal Core 金属磁芯
系列 型	SPM
状态	量产体制
品牌	TDK



	尺寸	
长度(L)	10.70mm ±0.50mm	
宽度(W)	10.00 mm ± 0.40 mm	
厚度 高低	4.00mm Max.	
推荐焊盘布局(A)	3. 80mm Nom.	
推荐焊盘布局(B)	6. 10mm Nom.	
推荐焊盘布局(C)	4. 80mm Nom.	

	电气特性
电感	$15\mu\mathrm{H}$ $\pm20\%$ at $100\mathrm{kHz}$
额定电流(基于L变化) [Typ.]	4.8A (20% Down)
额定电流(基于L变化) [Max.]	
额定电流(基于温度上升) [Typ.]	6.8A (40° C Rise)
额定电流(基于温度上升) [Max.]	
直流电阻 [Typ.]	40. 3m Ω
直流电阻 [Max.]	44. 4m Ω
自我共振频率 [Min.]	
自我共振频率 [Typ.]	
Q [Min.]	
Q [Typ.]	

	其他
使用温度范围(包括自我温度上升)	-40∼125° C
焊接方法	回流
汗按 方法	烙铁焊接
AEC-Q200	YES
包装形式	塑封编带 (330mm卷筒、帯宽 24mm)
包装个数	500pcs
重量	2. 13g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



RoHS Reach Halogen Free Pb Free




特性图表(这是参考数据,并不保证产品的特性。)


[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

Associated Images





[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.