

# SMD/SMT 电感器(线圈)

VLS4012HBX-R68M-N<sub>新产</sub>

品

RoHS Reach Halogen Free Pb Free

用途	一般等级
特点	Wire Wound 绕线
	Shield 磁屏蔽
	Metal Core 金属磁芯
系列   型	VLS-HBX
状态	量产体制
品牌	TDK



## 尺寸

长度(L)	4.00mm ±0.10mm
宽度(W)	4.00mm ±0.10mm
厚度   高低	1.20mm Max.
推荐焊盘布局(A)	1.30mm Nom.
推荐焊盘布局(B)	1.50mm Nom.
推荐焊盘布局(C)	4.40mm Nom.

## 电气特性

电感	680nH ±20% at 1MHz
额定电流(基于L变化) [Typ.]	7.78A (30% Down)
额定电流(基于L变化) [Max.]	7A (30% Down)
额定电流(基于温度上升) [Typ.]	5.95A (40° C Rise)
额定电流(基于温度上升) [Max.]	5.36A (40° C Rise)
直流电阻 [Typ.]	37mΩ
直流电阻 [Max.]	44mΩ
自我共振频率 [Min.]	
自我共振频率 [Typ.]	
Q [Min.]	
Q [Typ.]	

## 其他

使用温度范围(包括自我温度上升)	-40~105° C
焊接方法	回流
AEC-Q200	NO
包装形式	塑封编带 (180mm卷筒)
包装个数	1000pcs
重量	0.092g

! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

SMD/SMT 电感器(线圈)

VLS4012HBX-R68M-N<sub>新品</sub>

RoHS Reach Halogen Free Pb Free

---



特性图表(这是参考数据，并不保证产品的特性。)

SMD/SMT 电感器(线圈)

VLS4012HBX-R68M-N  
 新品

RoHS Reach Halogen Free Pb Free

Associated Images



! Images are for reference only and show exemplary products.  
 ! This PDF document was created based on the data listed on the TDK Corporation website.  
 ! All specifications are subject to change without notice.